

TABOS Series Electric Strike DES-2200

The DES-2200 is a compact, high performance electric strike designed for low profile openings where space is limited behind the jamb and for use with cylindrical & mortise locksets. The compact low profile design with an internally mounted solenoid and a field selectable fail secure / fail safe unit is easy to install.

Security Standards CE

All Doornics products conform to health, safety and environmental requirements laid down by the European CE of German TUV.



CE

Specifications

Input Voltage	DC12V, DC24V
Current Draw	DC12V@160mA±10% , DC24V@110mA ±10%
Dimension	176mm(L)x29mm(W)x26mm(H)
Monitoring Output	Micro switch (From "C") DC30V 1A (MAX)
Weight	500g

Features

- Duplex monitoring function for checking Lock & Door conditions.
- Continuous duty operation : Solenoid can be continuously powered.
- Choice of voltage 12V or 24VDC
- Low Current Consumption (DC12V@160mA±10%, DC24V@110mA±10%)
- Very easy to change the configuration of Fail-safe / Fail secure with only a screw.
- Non-handed
- Internal solenoid
- Tested to over one million cycles
- 2,200 lbs(1,000Kg) holding strength
- All stainless steel parts with durable diecast body for corrosion resistance.

DOORNICS CO., LTD.

SK Techno B/D No. 903, 16-4, Seongsu-Dong 1-Ga, Seongdong-Gu, Seoul, 133-112, Korea
 Tel : +82-2-3409-2590~4 Fax : +82-2-3409-2100
 E-mail : doornics@chollian.net Website : www.doornics.co.kr



The products are manufactured under an ISO 9001 & 2000 and Certified CE.