

TABOS Electric Strike DES-301M

The DES-301M is a compact, high performance electric strike designed for low profile openings where space is limited behind the jamb and for use with cylindrical & mortise locksets. The compact low profile design with an internally mounted solenoid and a field selectable fail secure / fail safe unit is easy to install.

Security Standards CE

All Doornics products conform to health, safety and environmental requirements laid down by the European CE of German TUV.

**CE** **Specifications**

Input Voltage	DC12V, DC24V
Current Draw	DC12V@300mA±10% , DC24V@170mA ±10%
Dimension	124mm(L)x31mm(W)x30mm(H)
Monitoring Output	Micro switch (From "C") DC30V 1A (MAX)
Weight	380g

 **Features**

- **Monitoring function**
- **Continuous duty operation : Solenoid can be continuously powered.**
- **Choice of voltage 12V or 24VDC**
- **Low Current Consumption (DC12V@300mA±10%, DC24V@170mA±10%)**
- **Very easy to change the configuration of Fail-safe / Fail secure with only a screw.**
- **Non-handed**
- **Internal solenoid**
- **ANSI compliant**
- **Tested to over one million cycles**
- **1,100 lbs(500Kg) holding strength**
- **Stainless steel Face Plate and Striker**
- **Compact Cast Zinc Alloy Body**

DOORNICS CO., LTD.

SK Techno B/D No. 903, 16-4, Seongsu-Dong 1-Ga, Seongdong-Gu,
Seoul, 133-112, Korea
Tel : +82-2-3409-2590~4 Fax : +82-2-3409-2100
E-mail : doornics@chollian.net Website : www.doornics.co.kr



The products are manufactured under an ISO 9001 & 2000 and Certified CE.