

TABOS Series Electric Strike DES-3200

The DES-3200 is a compact, high performance electric strike designed for low profile openings where space is limited behind the jamb and for use with cylindrical & mortise locksets. The compact low profile design with an internally mounted solenoid and a field selectable fail secure / fail safe unit is easy to install.

Security Standards CE

All Doornics products conform to health, safety and environmental requirements laid down by the European CE of German TUV.



CE

 **Specifications**

Input Voltage	DC12V, DC24V
Current Draw	DC12V@160mA±10% , DC24V@110mA ±10%
Dimension	202mm(L)x36.5mm(W)x29mm(H)
Monitoring Output	Micro switch (From "C") DC30V 1A (MAX)
Weight	600g

 **Features**

- Duplex monitoring function for checking Lock & Door conditions.
- Continuous duty operation : Solenoid can be continuously powered.
- Choice of voltage 12V or 24VDC
- Low Current Consumption (DC12V@160mA±10%, DC24V@110mA±10%)
- Very easy to change the configuration Fail-safe / Fail secure with only a screw.
- Non-handed
- Internal solenoid
- Tested to over one million cycles
- 2,200 lbs(1,000Kg) holding strength
- All stainless steel parts with durable diecast body for corrosion resistance.

DOORNICS CO., LTD.

SK Techno B/D No. 903, 16-4, Seongsu-Dong 1-Ga, Seongdong-Gu,
Seoul, 133-112, Korea
Tel : +82-2-3409-2590~4 Fax : +82-2-3409-2100
E-mail : doornics@chollian.net Website : www.doornics.co.kr



The products are manufactured under an ISO 9001 & 2000 and Certified CE.